



## eShield™ Specifications Sheet

eShield™ insulation greatly increases comfort in residential and commercial applications by reducing radiant heat gain. Able to stop more than 97-percent of radiant heat, eShield™ multilayer reflective foil insulation is an exceptionally efficient and innovative solution to thermal insulation needs. eShield™ insulation is a 3 layer composite comprised of a perforated foil facing, a Microlite fiberglass core and a reflective foil facing.

### Available sizes:

**24"x50'**

**48"x50'**

<b>Physical Properties</b>	<b>Values</b>	<b>Test Method</b>
Flame Spread	20	ASTM E84-10a
Smoke Developed	10	ASTM E84-10a
Full Scale Corner Room	PASS	UL 1715/UBC 26-3

<b>Thermal Performance</b>	<b>R Value</b>	<b>Test Method</b>
Heat Flow Down	R 12.82	ASTM C1363/C1224
Heat Flow Up	R 9.24	ASTM C1363/C1224
Heat Flow Horizontal	R 10.60	ASTM C1363/C1224



**Atlanta**  
4938 S Atlanta Rd. Ste. 700  
Smyrna, GA 30080  
678-646-1251

**Orlando**  
7101 Presidents Dr. Ste. 300  
Orlando, FL 32809  
407-286-4624